

Rugged PC/104 Enclosure System

Description

VPI Embedded's Rugged PC/104 Enclosure System provides an enclosure rated at an IP65 standard that houses PC/104-compatible devices. The Enclosure System is modular and can accommodate 1U, 2U, and 3U sized modules in between end caps.

Features

Enclosure Sealed to IP65 Standard

- Protection against rain and splashing water
- Protection against particle and dust ingress
- Protection against low pressure hosedown from any direction
- All segments are joined with an o-ring and labyrinth seal
- Submersion possible (with use of hermetic connectors)

Withstands Transportational Vibration and Shock

- Internal and external suspension systems
- Isolator geometry and material can be tailored for a specific application

Thermal Properties

- Conduction cooling for modules
- Optional internal circulation fans can be added to for high heat density applications
- Optional external fan/shroud system accelerates convection to ambient air

Flexibility and Modularity

- Compliant with PC/104 form factor
- Additional segments can be easily added
- System can be mission specific with highly tailored solutions



Part Numbers

The Rugged PC/104 Enclosure System entails the following part numbers:

- ENC-104 - 1U Height
- ENC-204 - 2U Height
- ENC-304 - 3U Height
- ENC-014 - Front End Cap
- ENC-024 - Rear End Cap

Contact Information

VPI Embedded
11814 S. Election Road, Ste 200
Draper, UT 84020
(801) 495-2310
info@vpiembedded.com

www.vpiembedded.com




Rugged PC/104 Enclosure System

Overview

The Rugged PC/104 Enclosure System (RES) is a robust packaging system that addresses the limitations of Commercial Off-The-Shelf (COTS) components when used in harsh environments such as those encountered in aerospace and military contexts.

PC/104 compatible processors and a wide selection of supporting components are produced in large volumes at very low cost. The compact form factor is attractive. General limitations of the COTS parts lie in shock, vibration, and humidity susceptibility. These limitations are addressed by the RES including:

- Water-tight
- Shock and vibration isolators
- Conduction cooling provision



2U Module

External Housing

- 6061-T6 Aluminum
- O-ring sealed

Internal Frame

- Provides structural support
- Acts as heat spreader and conduction path

COTS PCB

- Typical COTS PC/104 footprint board

Shock Isolators

- Internal shock isolators provide additional protection against shock and vibration

Thermal Strap

- Copper foil thermal strap provides conduction cooling link between board and external housing

Modularity



- Building blocks snap together
- Modules of different thickness accommodate PC/104 components
- End cap modules contain mounting provisions
- Modules share a common mate feature
- Modules can be snapped together in any order
- Units dovetail together for precise fit and optimum protection
- Interface between each module uses an o-ring seal

Specifications

Weight:

- Male End Cap: 0.5 lbs
- Female End Cap: 0.498 lbs
- 1U Housing: 0.461 lbs
- Internal Frame: 0.092 lbs
- Internal Bumper (4 required): 0.005 lbs
- External Bumper (4 required): 0.05 lbs

Dimensions:

- 1U Module: 6.4" x 6.2" x 0.762"
- 2U Module: 6.4" x 6.2" x 1.524"
- 3U Module: 6.4" x 6.2" x 2.286"

